

Thank you for choosing SRSDRIVE

Seat occupancy mat emulator as in PART 1 is compatible with Mercedes vehicles with **2-Wire Seat Occupancy Mats Only** and is designed to simulate the passenger in the seat. Belt simulator as in PART 2, is for bypassing seat belt warning light/alarm.
NOTE: With Seat Emulator installed do not fit a child seat to the front passenger seat

51 The Woods
Buncrana
Co. Donegal
F93 V226
Ireland
+44(0)7783725020 Email: support@srsdrive.com



PART 1. Seat Mat Bypass Installation

1. Ignition must remain off throughout the installation. Refer to the back of the page and set emulator switches as per compatibility table. Move the seat all the way up to gain the best access.
2. Under the seat at the front or back depending on model locate usually yellow/black colour main connector. Connector can be unclipped to gain better access. Look for smaller yellow plug with 2 black wires as in picture.



NOTE: If other colours are present then check the other side of the connector. Mercedes until around 2010 with 2 Wire seat occupancy mat systems future 2 black seat mat wires.



3. Disconnect original seat mat plug and connect our emulator instead.
4. Once all is connected turn on the ignition and wait approximately 1 min. Look at the instrument cluster, SRS light comes on and then goes off. For some variants, it clears automatically but for others, faults must be reset with proper diagnostics.

NOTE: In this Mercedes Emulator 2 LED's should be flashing.

NOTICE Customer satisfaction is our priority. If you are happy with your order please leave us **5-STAR Feedback or product review** and we'll do the same.


Problems with your order? Please contact us by eBay message, email or phone.

PART 2. Seat Belt Light/Chime Bypass Installation



For cars with Safety Belt warning light/chime

1. Ignition must remain off throughout the installation. Under the seat locate blue & yellow seat belt wires connected to the yellow main wiring harness.



2. Disconnect original seat mat plug and connect our seatbelt bypass.

NOTE: in case if your seat mat plug is a different shape and the one we supply is no good then remove the original plug and mount it on our seatbelt device.

3. Connect our seatbelt bypass and proceed with STEP 4 in part 1.

NOTE: Do not confuse it with the belt tensioner wires!

Troubleshooting

- If issue persists please check that dip switches are set correctly as per compatibility table as below.
- If SRS/Airbag light is still lit after installation then check other diagnostics faults. Emulator can't bypass unrelated faults such as those affecting ignition circuit, belt tensioner driver, airbag stage, etc. If other fault codes persist then take your car to the mechanic.
- If LED on emulator not flickering when device is connected, check the fuse and recheck connections to make sure that all are connected properly.
- If SRS/Airbag light return after some time of error-free use then clean all connections under the passenger and driver seats using a contact cleaner. Over time, oxidation causes connections to loose conductivity causing low or bad signal which is enough to trigger a fault code - airbag light.

THANK YOU!

All trademarks are the property of their respective owners.