

Start - TPMS light must be ON for it to connect successfully.

- Check that the Box has no Damage after Shipment.
- Make sure your vehicle is clear from RF - Radio Frequency interference such as garage door openers or any other aftermarket wireless sources.
- Open the lid and insert **2 X AA quality batteries like "Procell"** or similar but leave the lid open. Switch the unit ON, wait 30 seconds and LED on circuit board should be constantly on or start flashing - flashing in intervals.
- **Turn OFF the box** and place it close to the glove box, Driver side Fuse Box or closer to TPMS RX receiver location and follow one of the programming steps as below.

SRSDRIVE
51 The Woods
Buncrana
Co. Donegal F93 V226
Ireland

SRSDRIVE
auto electronics



Sales & Customer Support email:
Technical Support: support@tpmsbypass.com
Sales: sales@srsdrive.com

+44(0)7783725020 +353(0)838478878
Mon - Fri 9.00 – 17.00 Sat 10.00 – 2.00

For best prices and discounts visit:
www.tpmsbypass.com

1. Learn Procedure 104

Learn Procedure 104

1. Sensor Relearn Procedure without a Scan Tool:
2. Inflate all tires to the pressure listed on the placard.
3. Turn the ignition to the ON position, then the OFF position.
4. With the ignition OFF, wait 15 minutes.
5. Switch on BOX.
6. Drive the vehicle for at least 7~10 minutes at a speed of 30 MPH or more for the system to learn Box. Light out your good to Go.

2. Learn Procedure 105

Learn Procedure 105 for:

US Mazda Tribute year 2006
US Mazda Tribute year 2009 - 2011

1. Relearn Procedure for TPMS Box:
2. Inflate all tires to the pressure correctly.
3. Engage the Parking brake and turn ignition ON (engine off).
4. Switch on BOX.
5. Hold "Set" or ("ESP") button UP TO 5 minutes (located next to gear shift) until audio signal is heard. Audio signal confirms successful relearn. Light is out your good to go.

WARNING No adjustments are required on the PCB. The PCB has Sensitive Components therefore avoid contact with hands or metallic object as damage may occur to your unit and invalidate the Guarantee.

Happy with our product?

Great products deserve great reviews. Please take a minute of your time to write us a good Review and Feedback. On website please click on the purchased item and click on Reviews On eBay please go in your order history then select Write Review or leave Feedback or both.

Troubleshooting

- Reinsert the batteries and check that LED on PCB board is flashing (New quality batteries should last up to 12 months)
- Check manufacturing date and compare it with compatibility table in our ad. Manufacturing date can be different to registration date and box might not be compatible.
- Place the box close to the TPMS Receiver location usually, it's near the driver side fuse/smart junction box or glove box. If unsure, check TPMS Receiver location with the dealer.



**60 DAY MONEY BACK
GUARANTEE**



**QUALITY PRODUCTS
WITH WARRANTY**



**AFTER SALE
SUPPORT**